

--	--	--	--	--	--	--	--	--	--

**BARCH**  
**(SEM IV) THEORY EXAMINATION 2018-19**  
**ARCHITECTURAL STRUCTURES - IV**

Time: 3 Hours

Total Marks: 50

Notes:

- Attempt all Sections.
- Assume any missing data.

**SECTION – A**

Q1) Answer all the following in brief:

**(10X1=10)**

- a) Explain under reinforced beam.
- b) Define neutral axis.
- c) Discuss the effective width of flange.
- d) Define limit state method of design.
- e) Define characteristic strength of concrete.
- f) Draw stress-strain relationship for concrete in limit state method.
- g) Define maximum depth of neutral axis.
- h) Define development length.
- i) Define partial safety factor.
- j) Define shear reinforcement.

**SECTION – B**Q2) Attempt any **five** questions:**(5x5=25)**

- a) Differentiate between limit state method and working stress method and also discuss advantage of limit state method over working stress method.
- b) A beam, simply supported over an effective span of 7m carries a live load of 20 kN/m. Design the beam, using M20 concrete and HYSD bars of grade Fe415. Keep width equal to half the effective depth. Assume unit weight of concrete as 25kN/m<sup>3</sup>
- c) A cross section of a single reinforced concrete beam is 300mm wide and 400mm deep. The reinforcement bars consist of 4-16mm diameter. If the stress in concrete and steel do not exceed 5N/mm<sup>2</sup> and 140 N/mm<sup>2</sup>. Determine the moment of resistance of the section.
- d) Discuss in brief various types of cements used for construction.
- e) Differentiate between singly reinforced beam and doubly reinforced beam.
- f) Write and explain design steps for doubly reinforced beams.
- g) What do you understand by soil engineering? Discuss its advantages.
- h) Differentiate between one-way and two-way slab.

**SECTION – C**Q3) Attempt any **two** questions.**(2X7.5=15)**

- a) Draw stress diagram of concrete and steel in limit state method of design and derive the resultant force acting on stress block.
- b) A beam of effective span 8m carrying a u.d.l. of 18kN/m (factored) inclusive of self weight. Size of beam is 230mm X 400 mm. Determine the reinforcement. Use M-20 concrete and fe415 steel.
- c) Design the reinforcement for a reinforced concrete beam 300mm wide and 400mm deep of grade M20 to resist an ultimate moment of 150kN-m, using mild steel bars of grade Fe250.