

Printed Pages : 4



ECS-401

(Following Paper ID and Roll No. to be filled in your Answer Book)

PAPER ID : 110405

Roll No.

--	--	--	--	--	--	--	--	--	--

B. Tech.

(SEM. IV) THEORY EXAMINATION, 2014-15
COMPUTER ORGANIZATION

Time : 3 Hours]

[Total Marks : 100

- Note:**
- (1) Attempt all question.
 - (2) All question carry equal marks.

- 1 Attempt any FOUR questions. [4×5=20]
 - (a) Given the 8 bit data word 10110100, generate the 13 bit composite word for the hamming code that corrects single errors and detects double errors.
 - (b) What do you mean by high speed adder ? Discuss design of high speed adders.
 - (c) What is the radix of the numbers if the solution to the quadratic equation $x^2-10x+31=0$ is $x=5$ and $x=8$?
 - (d) Represent decimal number 8620 in (a) BCD; (b) excess-3 code; (c) 2421 code; (d) as a binary number.
 - (e) Design an arithmetic circuit with one variable S and two n bit data inputs A and B. The circuits generate the following four arithmetic operations in conjunction with the input carry C_{in} . Draw the logic diagram for the first two stages.

S	$C_{in} = 0$	$C_{in} = 1$
0	$D = A + B$ (<i>add</i>)	$D = A + 1$ (<i>increment</i>)
1	$D = A - 1$ (<i>decrement</i>)	$D = A + B' + 1$ (<i>subtract</i>)

- (f) What do you mean by Bus and explain bus interconnection ?
- 2 Attempt any FOUR questions. [4×5=20]
- (a) What are addressing modes? What is the need of having many addressing modes in your machine? Discuss indirect and register indirect addressing in details.
- (b) What is an array multiplier? Design an array multiplier that multiplies two 4-bit numbers. Use AND gates and binary adders.
- (c) What is ROM? How does PROM differ from EEPROM.
- (d) What is Stack Organization ? Compare register stack and memory stack ?
- (e) Specify the control word that must be applied to the processor to implement the following micro-operation.
- (1) $R1 \leftarrow R2 + R3$
 - (2) $R4 \leftarrow R4$
 - (3) $R5 \leftarrow R5 - 1$
 - (4) $R6 \leftarrow \text{shl } R1$
 - (5) $R7 \leftarrow \text{input}$
- (f) Draw the hardware details for Booth Multiplication algorithm and using Booth's Multiplication method multiply decimal number (-23) and (+9).

3 Attempt any TWO questions. [2×10=20]

- (a) Explain the difference between hardwired control and micro programmed control. Is possible to have a hardwired control associated with a control memory?
- (b) What is the meaning of the term one-address instruction ? How can an instruction, which requires three operands be executed in such machine ? Explain with the help of an example.
- (c) Write a program to evaluate the arithmetic statement:

$$X = \frac{A - B + C * (D * E - F)}{G + H * K}$$

- (1) Using an accumulator type computer with one address instruction.
- (2) Using a stack organized computer with zero address operation instructions.

4 Attempt any TWO question. [2×10=20]

- 1 (a) Explain LIFO, FIFO and CPU page replacement algorithm with example.
- (b) A virtual memory has a page size of 1K words. There are eight pages and four blocks. The associative memory page table contains the following entries.

<i>Page</i>	<i>Block</i>
0	3
1	1
4	2
6	0

Make a list of all virtual addresses (in decimal) that will cause a page fault if used by CPU.

- 2 A Computer employs RAM chips of 256×8 and ROM chips 1024×8 . The computer system needs 2K bytes of RAM, 4K bytes of ROM and 4 interface units, each with four registers. A memory mapped I/O configuration is used. The Two highest-order bits of the address bus are assigned 00 for RAM, 01 for ROM, and 10 for interface registers.
- (a) How many RAM and ROM chips are needed?
 - (b) Draw a memory address map for the system.
 - (c) Give the address range in hexadecimal for RAM, ROM and interface
- 3 What do you mean by memory management hardware? Explain the basic components of memory management unit.
- 5 Attempt any TWO questions. [2×10=20]
- (a) Describe asynchronous data transfer. What are the methods through which it can be achieved? Explain Stroke control and Handshaking.
 - (b) What are the various standard communication interfaces? Explain with the help of synchronous communication?
 - (c) Describe DMA with suitable block diagram, Why does DMA have priority over the CPU when both request a memory transfer? Explain.
-