

(Following Paper ID and Roll No. to be filled in your Answer Book)

**PAPER ID : 4071**

Roll No.

|  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|

**B.Tech**

**(SEM III) ODD SEMESTER THEORY EXAMINATION 2009-10  
STRENGTH OF MATERIAL**

Time : 3 Hours]

[Total Marks : 100

**Note :** Attempt all questions.

- 1 Attempt any two parts of the following :
- (a) Derive compatibility equations in Cartesian co-ordinates. 10
- (b) A solid circular shaft is required to carry a torque 40 kNm and a bending moment 30 kNm. If yield stress  $\sigma_y$  in a simple tensile test on a material of the shaft was found to be 260 N/mm<sup>2</sup>, find the minimum required diameter of the shaft according to different theories of failure. Take a factor of safety F.S. = 2.5 and Poisson's ratio = 0.3. 10
- (c) The state of stress at a point is given by the following array of terms : 10

$$\begin{bmatrix} 9 & 6 & 3 \\ 6 & 5 & 2 \\ 3 & 2 & 4 \end{bmatrix} \text{ MPa}$$

Determine the principal stresses and direction cosines of maximum principal stress.



Attempt any **two** parts of the following :

- (a) Mentioning Assumptions involved derive Bending Equation (Flexural formula). 10
- (b) The simply supported beam shown in Fig.1 has a flexural rigidity  $EI = 8 \times 10^6 \text{ Nm}^2$ . Find deflection at 'C' and 'D'. 10




Fig. 1

- (c) A hollow steel shaft 4 m long is to transmit 150 kW power at 150 RPM. The total angle of twist in this length is not to exceed  $2.5^\circ$  and the allowable shear stress  $60 \text{ N/mm}^2$ . Determine the inside and outside diameters, if  $N = 0.082 \times 10^6 \text{ N/mm}^2$ . 10

3 Attempt any **two** parts of the following :

- (a) Derive critical loads on the basis of Euler's method for column with both ends hinged. 10
- (b) A close-coiled helical spring is to have a stiffness of 100 N/m in compression, with a maximum load of 45 N and a maximum shearing stress of  $120 \text{ N/mm}^2$ . The solid length of the spring (i.e. coils touching) is 45 mm, find : 10
  - (i) The wire diameter
  - (ii) The mean coil radius and
  - (iii) The number of coils.

Take  $C = 0.4 \times 10^5 \text{ N/mm}^2$



(c) A short column of hollow cylindrical section has outer diameter 300 mm and inner diameter 200 mm and carries a load of 300 kN at a distance of 80 mm from the centre of the column.

- (i) Find the extreme stresses and draw the stress diagram.
- (ii) What should be the maximum eccentricity so that no tension develops in the column ?

4 Attempt any **two** parts of the following :

- (a) In a thin-walled cylindrical shell, determine **10**  
Hoop stress or circumferential stress,  
Longitudinal stress, Hoop strain and  
Longitudinal strain.
- (b) A spherical tank has a diameter of 20 m **10**  
and wall thickness 15 mm. If the permissible  
stress in the material is 120 MPa, find the  
maximum pressure at which a gas can be  
stored in the tank. Find the increase in  
diameter and volume of the tank due to  
the gas pressure. Take  $E = 200 \text{ GPa}$  and  
Poisson's ratio  $= 0.3$ .
- (c) A cylindrical pressure vessel of external and **10**  
internal radii 0.3 m and 0.2 m respectively  
is subjected to an internal hydraulic pressure  
of  $20 \text{ N/mm}^2$ . If  $E = 2 \times 10^5 \text{ N/mm}^2$  and  
 $\mu = 0.3$ , find the stresses at the internal and  
external surfaces and calculate the change  
in internal and external diameters.



- (a) Describe briefly : 10
- (i) Bending of beams with large initial curvature
  - (ii) Unsymmetrical bending.
- (b) A curved bar of rectangular cross-section has 10  
width 40 mm and depth 60 mm and has a radius of curvature 80 mm about the centroidal axis parallel to width. Find the bending stresses at the inner and outer faces caused by a moment of 500 Nm tending to increase the curvature.
- (c) For a channel section shown in Fig. 2, find 10  
the shear stress at the junction of the flange and the web and at the centre of the web due to a shear force of 50 kN. Locate the shear centre.




Fig. 2

