



- (c) Using Moment Area Method, determine the deflection  $\delta$  and slope  $\theta$  at the free end of a cantilever carrying a concentrated load  $P$  at the free end.
3. Answer any TWO of the following :— (6.5 × 2)
- (a) A slender column of length  $l$  is built in at its lower end  $A$  and laterally supported at its upper end. Find the first critical value of the compressive load  $P$ .
- (b) A boiler drum consists of a cylindrical portion 2m long, 1m diameter and 25 mm thick, closed by hemispherical ends. In a hydraulic test to  $10 \text{ N/mm}^2$ , how much additional water will be pumped in, after initial filling at atmospheric pressure? Assume the circumferential strain at the junction of cylinder and hemisphere is the same for both. For the drum material,  $E = 2,07,000 \text{ N/mm}^2$ ,  $\mu = 0.3$ . For water  $K = 2100 \text{ N/mm}^2$ .
- (c) Calculate the critical load of a strut, which is made of a bar circular in section and 5 m long and which is pin-jointed at both ends. The same bar when freely supported gives mid-span deflection of 10 mm with a 80 N load at the centre.
4. Answer any TWO of the following :— (6.5 × 2)
- (a) The cylinder of a hydraulic ram is of 6 cm internal diameter. Find the thickness required to withstand an internal pressure of  $40 \text{ N/mm}^2$ , if the maximum tensile stress is limited to  $60 \text{ N/mm}^2$  and the maximum shear stress to  $50 \text{ N/mm}^2$ .

- (b) Derive Lamé's equations to find out the stresses in thick spherical shells.
- (c) Explain any TWO of the following :—
  - (i) Stress concentration and notch sensitivity
  - (ii) Creep and Creep strength
  - (iii) Endurance limit

